

Application Serial No: 10/560,375
Responsive to the Office Action mailed on: February 6, 2008

RECEIVED
CENTRAL FAX CENTER

IN THE CLAIMS

APR 29 2008

Amendments To The Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An ultrasonic diagnostic apparatus, comprising:
 - ultrasonic wave transmission/reception means that transmits/receives an ultrasonic wave with respect to a subject;
 - a tomographic image processing part that forms a tomographic image representing a structure of the subject based on a reception signal;
 - a tissue characteristic image processing part that forms a tissue characteristic image representing a physical characteristic of a tissue of the subject through analysis of the reception signal of plural frames including at least one contraction and/or expansion period of the tissue;
 - memory means that stores the tomographic image and the tissue characteristic image, respectively;
 - an image composing part that combines at least the tomographic image and the tissue characteristic image;
 - display means that displays at least the tomographic image and the tissue characteristic image; and
 - control means that controls an operation of the ultrasonic wave transmission/reception means, the tomographic image processing part, the tissue characteristic image processing part, the memory means, the image composing part and the display means,
 - wherein during an operation of ultrasonic wave transmission/reception, the control means allows the tomographic image to be renewed in an arbitrary cycle, displayed by the display means, and stored in the memory means, while allowing the tissue characteristic image corresponding to at least one contraction and/or expansion period of the tissue to be renewed in a cycle different from the cycle for the tomographic

Application Serial No: 10/560,375
Responsive to the Office Action mailed on: February 6, 2008

image and corresponding to at least one contraction and/or expansion period of the tissue,
allowing the tissue characteristic image obtained for a period at least one cycle before
being displayed by the display means, and allowing the tissue characteristic image to be
stored in the memory means, and

 during a suspension of ultrasonic wave transmission/reception, the control means
allows arbitrary one of the tissue characteristic images that have been acquired previously
and one of the tomographic images that is in synchronization with the tissue
characteristic image to be read out from the memory means, respectively and displayed
by the display means.

2. (Original) The ultrasonic diagnostic apparatus according to claim 1, wherein the
display means is divided into a first display region and a second display region, and
displays at least the tomographic image in the first display region and at least the
tomographic image on which the tissue characteristic image is superimposed in the
second display region,

 during the operation of ultrasonic wave transmission/reception, the control means
allows the tomographic image to be displayed at least in the first display region of the
display means, while allowing the tissue characteristic image to be displayed in the
second display region of the display means, and

 during the suspension of ultrasonic wave transmission/reception, the control
means allows the tissue characteristic image and one of the tomographic images that is in
synchronization with the tissue characteristic image to be read out from the memory
means, respectively and displayed at least in the second display region of the display
means.

3. (Original) The ultrasonic diagnostic apparatus according to claim 2, wherein
during the operation of ultrasonic wave transmission/reception, one of the tomographic
images that is in synchronization with the tissue characteristic image is displayed in the
second display region.

4. (Original) The ultrasonic diagnostic apparatus according to claim 2, wherein

Application Serial No: 10/560,375
Responsive to the Office Action mailed on: February 6, 2008

during the suspension of ultrasonic wave transmission/reception, one of the tomographic images that is in synchronization with the tissue characteristic image is displayed in the first display region.

5. (Original) The ultrasonic diagnostic apparatus according to claim 2, wherein during the suspension of ultrasonic wave transmission/reception, the tissue characteristic image that is obtained based on a time period in which the tomographic image displayed in the first display region is included and the tomographic image that is in synchronization with the tissue characteristic image are displayed superimposedly in the second display region.

6. (Original) The ultrasonic diagnostic apparatus according to claim 1, wherein the image composing part allows a related waveform that contains information corresponding to at least one of the tomographic image and the tissue characteristic image to be displayed on a display screen of the display means in such a manner as to be combined with the tomographic image and the tissue characteristic image, and

 during the suspension of ultrasonic wave transmission/reception, the control means allows a portion of the related waveform to be displayed in a highlighted manner, which corresponds to a time period in which the tissue characteristic image being displayed is formed.

7. (Original) The ultrasonic diagnostic apparatus according to claim 1, wherein the tissue characteristic image is an elastic modulus image.

8. (Original) The ultrasonic diagnostic apparatus according to claim 1, wherein the tissue characteristic image is an image representing a strain or a strain rate.

9. (Original) The ultrasonic diagnostic apparatus according to claim 1, wherein the tissue characteristic image is an image representing a viscosity.